



GX470 Height Control RAM Mount

Installation Instructions

Tools

3D Printed Panel Tool
2.5mm Allen Wrench
3mm Allen Wrench

Product ID SMK01210

Document Updated 4/7/2024

Installation Difficulty Easy

Step 1



Remove the two M5 screws in the center of the unit to install the provided Ram Mount, these need to be snug but not overly tight. Make sure all the cams are tight and tucked up into the body of the mount as shown.

Step 2



Use the Provided panel tool to remove the height control. There are 4 tabs that need to be released (see next image). You will need to pry softly between the wood and height control.

Step 3



The tabs that need to be released to remove the unit, once removed undo the bottom connector plug to remove from the center console

Step 4



Make sure your bracket looks as shown, all the cams should be tight to the body and the Ram Mount secured on top

Step 5



Drop the unit into the pocket and use a 2.5mm allen wrench (Tee handle preferred) to loosen each bolt. You should spin each one 3 FULL rotations to ensure they are floating freely

Step 6



With a swift motion "flick" the bolts clockwise, this will cause the cams to spin out and lift up to secure the bracket to the panel. Once you flick it out you'll be able to tighten each one

Step 7



Once you begin to tighten each corner you can pull up on the ball mount to check each corner is secure, once all four are engaged give them a snug tighten and you are good to go! Now mount your accessories and enjoy the trails!